		SATCO NUVO
Project Name		
Location	Prepared By	
=		
CATCO	1100F	
SATCO S 4W/LED/T5/840/BP	11902	

Notes

110-27-2025 05

Status	Active	
Watts	4W	
Incandescent Equivalent	25W	
Fluorescent Equivalent	8W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T5	
Base	Miniature Bi Pin	
ANSI Base	G5	
Nominal Length	12	
Finish	Frost	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80+	
Lumens	400L	
Beam Spread	240	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical		
Ballasting Requirements	No ballast or external driver required	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	20%	
Operating Temperature	-25C (-13F) to +45C (+113F)	

Physical	
MOL	11.91
MOD	0.83
Material	Glass
Lens Finish	Frost
Weight (lb.)	0.13

Additional Information		
Additional Info	Replaces F8T5/CW lamps	
Shatter-Proof Type	PET Coated	
Installation Notes	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance		
Safety Listing	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component	
Location Rating	Damp	
DLC Approved	No	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	Yes	
SDS Sheet	LED_Lamp	