SATCO NUVO

Project Name

Prepared By



SATCO S11922

13.5T8/LED/48-840/DIM-BP

Notes

General	
Status	Discontinued
Substitute	S11664
Watts	13.5W
Incandescent Equivalent	70W
Fluorescent Equivalent	25W
Volts	120V
Ballast Type	Туре В
Shape	<u>T8</u>
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	1800L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
	Ballast Bypass; Direct wire 120V line voltage;
Ballasting Requirements	No ballast or external driver required
Dimming Type	Reverse Phase or Phase Selectable
Power Factor	0.9
ТНО	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Operating Temperature	
Operating Temperature Physical	-20C (-4F) to +45C (+113F)
Operating Temperature Physical MOL	-20C (-4F) to +45C (+113F) 48
Operating Temperature Physical MOL MOD	-20C (-4F) to +45C (+113F) 48 1
Operating Temperature Physical MOL MOD Material	-20C (-4F) to +45C (+113F) 48 1 Glass
Operating Temperature Physical MOL MOD Material Lens Finish	-20C (-4F) to +45C (+113F) 48 1 Glass Frost
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use Installation Notes	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture	-20C (-4F) to +45C (+113F) 48 1 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (Ib.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes S-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale in California
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale in California Lawful for sale
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes S-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Yes S-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Yes S-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale Lawful for sale
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status Vermont Status Washington Status RoHS Compliant	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale in California Lawful for sale Lawful for sale Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status RoHS Compliant FCC Compliant	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Yes S-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale in California Lawful for sale Lawful for sale Yes Yes
Operating Temperature Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Tube Guard Use Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved DLC ID California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status RoHS Compliant	-20C (-4F) to +45C (+113F) 48 1 Glass Frost Glass White 0.45 Yes Yes Not for use in vapor tight fixtures. Install only in non-shunted lampholders Yes 5-Years CULus - Classified; cULus - Certified Damp Yes PLCHL8NP6U2O Lawful for sale in California Lawful for sale Lawful for sale Yes

