

Project Name

Location

Prepared By



SATCO S11942

23T5/LED/48-835/XD

Notes

(www) 08-02-2023 00:44:11

General

Status	Active
Watts	23W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W
Volts	120V-277V
Ballast Type	Type C
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	3400L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast replaced with external driver
Operating Frequency	50/60Hz
Dimming Note	0-10V Dimming Only
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	48
MOD	0.63
Material	Glass
Lens Finish	Frost
Housing Color	None
Weight (lb.)	0.31

Additional Information

Additional Info	Not for emergency lighting
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLQCYU7LBNEU
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)
SDS Sheet	LED_Lamp