SATCO NUVO

Project Name

Location Prepared By



N		ha	~
II.	(0)	L =	-

www] 01-15-2024 02:40:0

General	
Status	Discontinued
Substitute	S21239
Watts	6.5W
Incandescent Equivalent	60W
Volts	120V
Shape	G25
Base	Medium
ANSI Base	E26
Finish	Soft White
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	80
Lumens	650L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Lamp Type	Globe
Technology	LED
Electrical	
Operating Frequency	50-60Hz
Operating Frequency Power Factor	50-60Hz >0.7
Power Factor	>0.7
Power Factor Operating Position	>0.7 Universal
Power Factor Operating Position Operating Temperature	>0.7 Universal
Power Factor Operating Position Operating Temperature Physical	>0.7 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5
Power Factor Operating Position Operating Temperature Physical MOL MOD	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09 Yes 3 Year Limited
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09 Yes 3 Year Limited
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09 Yes 3 Year Limited CULus Damp
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09 Yes 3 Year Limited CULus Damp No
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star CA T20 / T24 Rationale	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09 Yes 3 Year Limited cULus Damp No Non-Compliant - <82 CRI
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating Energy Star CA T20 / T24 Rationale California Status	>0.7 Universal -20C (-4F) to +45C (+113F) 4.5 3.13 0.09 Yes 3 Year Limited cULus Damp No Non-Compliant - <82 CRI Non-Compliant