SATCO NUVO

Project Name

ocation Prepared By



Notes

1 10-21-2025 23:30:

General	
Status	Discontinued
Substitute	S16439
Watts	32W
Incandescent Equivalent	125W
Fluorescent Equivalent	100W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	84
Finish	Frost
CCT (Kelvin)	6500K
Temperature	Daylight
CRI	80+
Lumens	4500L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60Hz	
Power Factor	0.9	
Operating Temperature	-30C (-22F) to +45C (+113F)	

Physical	
MOL	81.88
MOD	1
Material	Plastic
Lens Finish	Frost
Lens Material	Nano
Housing Color	White
Weight (lb.)	1.32

Additional Information		
Tube Guard Use	No	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	No
UL Application	Tubes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp