SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	4W
Incandescent Equivalent	
Volts	120V
Shape	
Base	Bayonet Double Contact
ANSI Base	BA15d
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	90+
Lumens	360L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Tubular
Technology	LED
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz >0.7
Power Factor	>0.7
Power Factor Operating Temperature Physical	>0.7 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	>0.7 -20C (-4F) to +45C (+113F) 5.12
Power Factor Operating Temperature Physical MOL MOD	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79
Power Factor Operating Temperature Physical MOL MOD Housing Color	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79
Power Factor Operating Temperature Physical MOL MOD Housing Color	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05 Yes Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05 Yes Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05 Yes Not for use in vapor tight fixtures. 2-Years
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05 Yes Not for use in vapor tight fixtures. 2-Years cRUus - Recognized Component
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing Location Rating	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05 Yes Not for use in vapor tight fixtures. 2-Years cRUus - Recognized Component Wet
Power Factor Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing Location Rating UL Application	>0.7 -20C (-4F) to +45C (+113F) 5.12 0.79 Frost 0.05 Yes Not for use in vapor tight fixtures. 2-Years cRUus - Recognized Component Wet Filament LED Lamp

