## SATCO NUVO

Project Name

ocation Prepared By



Notes

ww1 10-27-2025 05:20:5

General	
Status	Discontinued
Substitute	S21849
Watts	4.5W
Incandescent Equivalent	40W
Volts	120V
Shape	CA10
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	350L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Power Factor	0.7
Power Factor Operating Position	Universal
	· · · · · · · · · · · · · · · · · · ·
Operating Position	Universal
Operating Position Operating Temperature	Universal
Operating Position Operating Temperature Physical	-20C (-4F) to +40C (+104F)
Operating Position Operating Temperature Physical MOL	Universal -20C (-4F) to +40C (+104F) 3.88
Operating Position Operating Temperature  Physical  MOL  MOD	Universal -20C (-4F) to +40C (+104F)  3.88 1.38
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)	Universal -20C (-4F) to +40C (+104F)  3.88 1.38
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information	Universal -20C (-4F) to +40C (+104F)  3.88  1.38  0.04
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing Location Rating	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating California Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating California Status  Title 20 / 24 Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating California Status  Title 20 / 24 Status  Colorado Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status  Hawaii Status Nevada Status Vermont Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Position Operating Temperature  Physical  MOL  MOD  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status  Vermont Status  Washington Status  Washington Status	Universal -20C (-4F) to +40C (+104F)  3.88 1.38 0.04  Yes 2-Years  CULus Damp Non-Compliant Non-Compliant Lawful for sale