## SATCO NUVO

Project Name

Location

Prepared By



**SATCO S21876** 4.5G16.5/LED/WH/950/120V/E12/2

Notes

| General   |   |
|---|---|
| Status  | Active  |
| Watts   | 4.5W  |
| Incandescent Equivalent   | 40W   |
| Volts   | 120V  |
| Shape   | G16.5   |
| Base  | Candelabra  |
| ANSI Base   | E12   |
| Finish  | White   |
| CCT (Kelvin)  | 5000K   |
| Temperature   | Natural Light   |
| CRI   | 90+   |
| Lumens  | 350L  |
| Beam Spread   | 320   |
| Dimmable  | Yes-Dimmable  |
| Dimming Note  | 120V only   |
| Hours Rated   | 15000   |
| Product Category  | Globe   |
| Technology  | LED   |
| Smart Product Info  |   |
| IOT Enabled   | No  |
| Integrated Camera   | No  |
| Electrical  |   |
|   |   |
| Operating Frequency   | 60Hz  |
| Operating Frequency<br>Power Factor   | 60Hz<br>0.76  |
| Operating Frequency<br>Power Factor<br>Operating Position   |   |
| Power Factor  | 0.76  |
| Power Factor<br>Operating Position<br>Operating Temperature   | 0.76<br>Universal   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical   | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL<br>MOD   | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Housing Color  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Housing Color<br>Weight (lb.)  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97   |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Housing Color<br>Weight (lb.)<br>Additional Information<br>Rated For Enclosed Fixture  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes  |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Housing Color<br>Weight (lb.)<br>Additional Information<br>Rated For Enclosed Fixture<br>Warranty  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07   |
| Power Factor<br>Operating Position<br>Operating Temperature<br>Physical<br>MOL<br>MOD<br>Housing Color<br>Weight (lb.)<br>Additional Information<br>Rated For Enclosed Fixture  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years   |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>cETLus - Listed  |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing   Location Rating  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>cETLus - Listed<br>Wet   |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing   Location Rating   UL Application   | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>cETLus - Listed<br>Wet<br>Filament LED Lamp  |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing   Location Rating   UL Application   California Status   | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>cETLus - Listed<br>Wet<br>Filament LED Lamp<br>Lawful for sale in California                           |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing   Location Rating   UL Application   California Status   Title 20 / 24 Status                  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>cETLus - Listed<br>Wet<br>Filament LED Lamp<br>Lawful for sale in California<br>Lawful for sale        |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing   Location Rating   UL Application   California Status   Title 20 / 24 Status   RoHS Compliant | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>CETLus - Listed<br>Wet<br>Filament LED Lamp<br>Lawful for sale in California<br>Lawful for sale<br>Yes |
| Power Factor   Operating Position   Operating Temperature   Physical   MOL   MOD   Housing Color   Weight (lb.)   Additional Information   Rated For Enclosed Fixture   Warranty   Compliance   Safety Listing   Location Rating   UL Application   California Status   Title 20 / 24 Status                  | 0.76<br>Universal<br>-20C (-4F) to +45C (+113F)<br>3.11<br>1.97<br>None<br>0.07<br>Yes<br>2-Years<br>cETLus - Listed<br>Wet<br>Filament LED Lamp<br>Lawful for sale in California<br>Lawful for sale        |

