SATCO NUVO

Project Name

Location

Prepared By



Notes

3 04 45 0004 00 40

General	
Status	Discontinued
Substitute	S49393
Watts	45W
	300W
Incandescent Equivalent	65W
Fluorescent Equivalent	175W
HID Equivalent Volts	173W 100V-277V
	Corncob
Shape	
ANSI Base	Mogul Extended EX39
Finish	Clear
	5000K
CCT (Kelvin)	
Temperature	Natural Light
CRI	80+
Lumens	6000L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
	AC 90-305V
Working Voltage Operating Frequency	AC 90-305V 50/60Hz
Working Voltage	
Working Voltage Operating Frequency	50/60Hz
Working Voltage Operating Frequency Power Factor	50/60Hz 0.9
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature	50/60Hz 0.9 Base Up or Down
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light /
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg)
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes IP65
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes IP65
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro cULus - Listed Wet
Working Voltage Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F) 10.66 3.66 Clear White/Grey 2.15 Replaces HID, CFL, and Incandescent; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro CULus - Listed Wet No

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



