

Notes

w1 08-01-2025 00:10:0

Status	Active	
Watts	25W	
Incandescent Equivalent	100W	
Fluorescent Equivalent	54W	
Volts	Ballast Dependent	
Ballast Type	Туре А	
Shape	T5	
Base	Miniature Bi Pin	
ANSI Base	G5	
Nominal Length	48	
Finish	Gloss	
CCT (Kelvin)	5000K	
Temperature	Natural Light	
CRI	80+	
Lumens	3500L	
Beam Spread	185	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast required
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	46
MOD	0.63
Material	Aluminum / Glass
Lens Finish	Gloss
Housing Color	None
Weight (lb.)	0.3

Additional Information		
Additional Info	Light Emitting Area of 325 degrees; System Wattage (Type A) - 28W	
Includes	Integrated thermal fuse at pins	
Integrated Features	Integrated thermal fuse at pins	
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PL2M6895FL33
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp