SATCO NUVO

Project Name

ocation Prepared By



Notes

w1 08-26-2025 22:39:1

General	
Status	Discontinued
Substitute	S21262
Watts	2.5W
Incandescent Equivalent	25W
Volts	120V
Shape	B11
ANSI Base	Candelabra E12
Finish	Clear
CCT (Kelvin)	2700K
	Warm White
Temperature CRI	80+
Lumens Roam Spread	360
Beam Spread	
Dimmable Hours Rated	Yes-Dimmable
	15000 Condia
Product Category	Candle LED
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	60Hz 0.9
Power Factor	0.9
Power Factor Operating Position	0.9 Universal
Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F) 3.88
Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status Vermont Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale Lawful for sale Lawful for sale



LED_Lamp

FCC Compliant SDS Sheet