SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Discontinued
Substitute	S21262
Watts	2.5W
Incandescent Equivalent	25W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	200L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Electrical Operating Frequency	60Hz
	60Hz 0.9
Operating Frequency	
Operating Frequency Power Factor	0.9
Operating Frequency Power Factor Operating Position	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years cULus Damp
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status California Compliant Substitute Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant S29877 Lawful for sale Lawful for sale

