SATCO NUVO

Project Name

ocation

Prepared By



Notes

rwl 10-10-2025 00:17:3

General	
Status	Discontinued
Substitute	S49670
Watts	18W
Incandescent Equivalent	120W
Fluorescent Equivalent	32W
HID Equivalent	70W
Volts	120V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	2340L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 6 in. Width: 8.5 in. Height: 6 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	

Electrical	
Working Voltage	AC 90-305V
Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 2.5KV
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	5.69
MOD	2.38
Lens Finish	Clear
Lens Material	Plastic (PS)
Housing Color	White
Weight (lb.)	0.66

Additional Info	Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	DLC 5.1 replacement S23146; Non-DLC replacement S49670
Installation Notes	Not for use in vapor tight fixtures.
Shatter-Proof Type	Shatter resistant materials
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

