SATCO NUVO

Project Name

Location

Prepared By



www] 05-15-2024 04:42:5

General	
	Discontinued
Status	Discontinued
Substitute Watts	S28987 60W
	300W
Incandescent Equivalent	250W
HID Equivalent Volts	100V-277V
	Corncob
Shape Base	
ANSI Base	Mogul E39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	9000L
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
recimology	Length: 11 in. Width: 8 in. Depth:
Min Compartment Size	8 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Power Factor	>0.9
I UWEI I AUIUI	>0.3
Operating Position	Horizontal
Operating Position	Horizontal
Operating Position Surge Protection	Horizontal Built-in surge protection - 4KV
Operating Position Surge Protection Operating Temperature Physical	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)
Operating Position Surge Protection Operating Temperature Physical MOL	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63
Operating Position Surge Protection Operating Temperature Physical MOL MOD	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures.
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures.
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures.
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified Damp
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified Damp No
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified Damp No No
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified Damp No No Exempt - Base Not Regulated
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified Damp No No Exempt - Base Not Regulated Lawful for sale in California
Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status	Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 10.63 3.13 Clear White Yes IP64 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cUL - Classified; cUL - Certified Damp No No Exempt - Base Not Regulated Lawful for sale Lawful for sale

Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED_Lamp	

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



