		SATCO NUVO
Project Name		
Location	Prepared By	
	<u> </u>	
-		
6.1 -66		
SATCC 23PLL/LED/840/BP	S9951	

Notes

rw] 10-21-2025 23:30

Status	Active
Watts	23W
Fluorescent Equivalent	40W
Volts	120V-277V
Ballast Type	Туре В
Shape	T5
Base	2G11
ANSI Base	2G11
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2800L
Beam Spread	270
Hours Rated	50000
Product Category	PL
Operating Position	Universal
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass

Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	
Physical		
MOL	22.5	
MOD	0.63	
Housing Color	White	

50/60Hz

Additional Information				
Additional Info	CCT Selectable Option: S18423			
Installation Notes	Not for use in vapor tight fixtures.			
Rated For Enclosed Fixture	Yes			
Warranty	5-Years			

0.38

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	Yes
DLC ID	PL2ISZU5GTZN
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Operating Frequency

Weight (lb.)