

Project Name

Location

Prepared By

## General

Status	Discontinued
Substitute	S11622R1
Wattage	12W
Voltage	120V
Finish	Black
CCT (Kelvin)	3000K
Color Temperature	Warm White
Lumen Output	850L
Indoor or Outdoor Fixture	Indoor

## Specifications

Technology	LED
CRI	90+
Beam Angle	40
Rated Hours	50000
Operating Temperature	-20C (-4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Sloped Ceiling	Yes

## Dimensions

Length (in.)	4.88
Width (in.)	4.88
Height (in.)	2
Weight (lb.)	1.47

## Compliance

Safety Listing	cETLus - Listed
Location Rating	Wet
UL Application	Ceiling
ENERGY STAR	No
DLC Approved	No
Air Tight Rated	Yes
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

## Additional Information

Additional Information	Integrated j-box for direct wire installation
Specification Note	Aiming Angle: 30dg
Installation Notes	*If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)
Warranty	5-Years



## SATCO S11622

12WLED/DW/GBL/4/930/SQ/RD/BK

## Notes

(www) 05-07-2023 00:43:13