

Project Name

Location

Prepared By



**SATCO S11626**

12WLED/DW/GBL/3/930/RND/RD/BN

**Notes**

(www) 03-10-2023 09:50:06

**General**

Status	Discontinued
Substitute	S11626R1
Wattage	12W
Voltage	120V
Finish	Brushed Nickel
CCT (Kelvin)	3000K
Color Temperature	Warm White
Lumen Output	840L
Indoor or Outdoor Fixture	Indoor

**Specifications**

Technology	LED
CRI	90+
Beam Angle	40
Rated Hours	50000
Operating Temperature	-20C (-4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Sloped Ceiling	Yes

**Dimensions**

Width (in.)	4.38
Height (in.)	3
Weight (lb.)	1.29

**Compliance**

Safety Listing	cETLus - Listed
Location Rating	Wet
UL Application	Ceiling
Energy Star	No
DLC Approved	No
Air Tight Rated	Yes
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

**Additional Information**

Additional Information	Integrated j-box for direct wire installation
Specification Note	Aiming Angle: 15dg
Installation Notes	*If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)
Warranty	5 Year Limited - Fixtures