

Project Name

Location

Prepared By



SATCO S11925

43T8/LED/96-865/BP 120-277V

Notes

[www] 10-11-2021 02:00:30

General

Status	Active
Watts	43W
Fluorescent Equivalent	54W/59W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	Gloss White
CCT (Kelvin)	6500
Temperature	Daylight
CRI	82
Lumens	5500L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	96
MOD	1
Lens Finish	Gloss White

Additional Information

Additional Info	All glass tube
Shatter-Proof Type	Shatterproof coated
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes