SATCO NUVO

Project Name

Location

Prepared By



SATCO S39674

54W/LED/HID/4K/100-277V/EX39

Notes

www] 05-15-2024 04:42:

Compliance

General	
Status	Discontinued
Substitute	S49674
Watts	54W
Incandescent Equivalent	300W
Fluorescent Equivalent	85W
HID Equivalent	250W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	7560L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 15.75 in. Width: 8 in. Depth: 8 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
	AC 100-277V
Working Voltage	AC 100-277V 50/60Hz
Working Voltage Operating Frequency Power Factor	50/60Hz >0.9
Working Voltage Operating Frequency Power Factor Operating Position	50/60Hz >0.9 Base Up or Down
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection	50/60Hz >0.9
Working Voltage Operating Frequency Power Factor Operating Position	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS)
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White 1.89 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White 1.89 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White 1.89 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White 1.89 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23142;
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Specification Note	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 9.03 3.34 Clear Plastic (PS) White 1.89 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23142; Non-DLC replacement S49674

Safety Listing	cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



