SATCO NUVO

Project Name

Location

Prepared By



SATCO S9676

100W/LED/HID/40K/100-277V EX39

Notes

www] 01-15-2024 02:40:1

California Status

Conoral	
General	
Status	Discontinued
Substitute	S49676
Watts	100W
Incandescent Equivalent	500W
Fluorescent Equivalent	150W
HID Equivalent	400W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	13000L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
	AC 90-305V
Working Voltage	AC 90-305V 50/60Hz
Working Voltage Operating Frequency Power Factor	50/60Hz
Working Voltage Operating Frequency Power Factor Operating Position	50/60Hz 0.95 Universal
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection	50/60Hz 0.95 Universal Built-in surge protection
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature	50/60Hz 0.95 Universal
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection	50/60Hz 0.95 Universal Built-in surge protection
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature	50/60Hz 0.95 Universal Built-in surge protection
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F)
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture IP Rating	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes IP65
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture IP Rating Warranty	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes IP65
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture IP Rating Warranty Compliance	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes IP65 5 Year Limited - Hi-Pro
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes IP65 5 Year Limited - Hi-Pro CULus - Classified; cULus - Certified
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes IP65 5 Year Limited - Hi-Pro cULus - Classified; cULus - Certified Damp
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information Includes Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star	50/60Hz 0.95 Universal Built-in surge protection -20C (-4F) to +65C (+149F) 9.63 5.88 Clear White Safety chain Yes IP65 5 Year Limited - Hi-Pro cULus - Classified; cULus - Certified Damp No

Lawful for sale in California

Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



