

Project Name

Location

Prepared By



Notes

[www] 02-00-0025 01-20-13

General

| | |
|---------------------------|-------------------------------|
| Status | Active |
| Fixture Type | Surface Mount |
| Finish | White |
| Wattage | 42W |
| Lumen Output | 2850L-3100L |
| CCT (Kelvin) | 2700K/3000K/3500K/4000K/5000K |
| Indoor or Outdoor Fixture | Indoor |

Specifications

| | |
|-----------------------|-----------------------------------|
| Technology | LED |
| Color Temperature | Warm White to Natural Light |
| CRI | 90 |
| Voltage | 120V/277V |
| Beam Angle | 110 |
| Rated Hours | 50000 |
| Operating Temperature | -20C (-4F) to +40C (+104F) |
| Dimmable | Yes-Dimmable |
| Dimming Note | 120V only |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Surge Protection | Built-in surge protection - 2.5KV |
| Weight (lb.) | 5.43 |
| Material | Die-Cast Aluminum |

Dimensions

| | |
|--------------|-------|
| Height (in.) | 1.06 |
| Width (in.) | 5.61 |
| Length (in.) | 47.72 |

Compliance

| | |
|----------------------|-------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Damp |
| Energy Star | No |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | California T24 Listed |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| Flicker Free | No |
| SDS Sheet | LED_Fixture |

Additional Information

| | |
|------------------------|---|
| Additional Information | UGR - 21.5; Hi pot - DC-1550V; Edge-lit - Yes |
| Installation Notes | Compatible with 3" & 4" J-box and pancake J-box |
| Warranty | 5 Year Limited - Fixtures |