


Project Name

Location

Prepared By



NUVO 65-571R1

2X2 LED BACKLIT FLAT PANEL

Notes

[\[www\] 02-00-0000-01-20-27](#)

General

| | |
|---------------------------|--------------------|
| Status | Active |
| Fixture Type | Backlit Flat Panel |
| Finish | White |
| Wattage | 20W/30W/40W |
| Lumen Output | 2200L-4600L |
| CCT (Kelvin) | 3500K/4000K/5000K |
| IP Rating | IP20 |
| Indoor or Outdoor Fixture | Indoor |
| Panel Size | 2x2 |

Smart Product Info

| | |
|-------------|----|
| IOT Enabled | No |
|-------------|----|

Specifications

| | |
|-----------------------|---------------------------------|
| Technology | LED |
| Color Temperature | Warm to Cool White |
| CRI | 80+ |
| Voltage | 120V-277V |
| Beam Angle | 120 |
| Rated Hours | 50000 |
| Operating Temperature | -17C (+1.4F) to +45C (+113F) |
| Dimmable | Yes-Dimmable |
| Dimming Note | 0-10V Dimming Only |
| Photocell or Sensor | No Photocell |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Surge Protection | Built-in surge protection - 2KV |
| Weight (lb.) | 4.85 |
| Material | Aluminum / Steel |

Dimensions

| | |
|--------------|-------|
| Height (in.) | 1.5 |
| Width (in.) | 23.75 |
| Length (in.) | 23.75 |

Compliance

| | |
|----------------------|-------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Damp |
| UL Application | LED Panel Luminaire |
| Energy Star | No |
| DLC Approved | Yes |
| DLC ID | S-GXP8L0 |
| NSF Approved | Yes |
| Air Tight Rated | No |
| IC Rated | Yes |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| Flicker Free | Yes |
| SDS Sheet | LED_Fixture |

Additional Information

| | |
|------------------------|-----------------------------------------|
| Additional Information | Driver Specs - VDC38-48V; 430/620/810mA |
| Warranty | 5 Year Limited - Fixtures |