

Project Name

ocation Prepared By



NUVO 65-576R1

2X4 LED EM BACKLIT FLAT PANEL

Notes

rw] 02-19-2025 00:5

Dimensions Height (in.)

Width (in.)

Length (in.)

Status	Active	
Fixture Type	Backlit Flat Panel	
Finish	White	
Wattage	30W/40W/50W	
Lumen Output	3300L-5750L	
CCT (Kelvin)	3500K/4000K/5000K	
IP Rating	IP20	
Indoor or Outdoor Fixture	Indoor	
Panel Size	2x4	

IOT Enabled	No	
Specifications		
Technology	LED	
Color Temperature	Warm to Cool White	
CRI	80+	
Voltage	100V-277V	
Beam Angle	120	
Rated Hours	50000	
Operating Temperature	-17C (+1.4F) to +45C (+113F)	
Dimmable	Yes-Dimmable	
Dimming Note	0-10V Dimming Only	
Photocell or Sensor	No Photocell	
Lens Material	Poly methyl methacrylate (PMMA)	
Surge Protection	Built-in surge protection - 2KV	
Weight (lb.)	12.13	
Material	Aluminum / Steel	

3.06

23.75

47.72

Compliance	
Safety Listing	cETLus - Listed
Location Rating	Damp
UL Application	LED Panel Luminaire
Energy Star	No
DLC Approved	Yes
DLC ID	S-U7LTOR; S-C51JHR
NSF Approved	Yes
Air Tight Rated	No
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Driver Specs - VDC38-48V; 630/810/1030mA
Warranty	5 Year Limited - Fixtures

