

Project Name

Prepared By



2X2 LED BACKLIT FLAT PANEL

Notes

Weight (lb.) Material

Status	Active	
Fixture Type	Backlit Flat Panel	
Finish	White	
Wattage	20W/30W/40W	
Lumen Output	2200L-4600L	
CCT (Kelvin)	3500K/4000K/5000K	
IP Rating	IP20	
Indoor or Outdoor Fixture	Indoor	
Panel Size	2x2	

IOT Enabled	No	
Specifications		
Technology	LED	
Color Temperature	Warm to Cool White	
CRI	80+	
Voltage	120V-347V	
Beam Angle	120	
Rated Hours	50000	
Operating Temperature	-17C (+1.4F) to +45C (+113F)	
Dimmable	Yes-Dimmable	
Dimming Note	0-10V Dimming Only	
Photocell or Sensor	No Photocell	
Lens Material	Poly methyl methacrylate (PMMA)	
Surge Protection	Built-in surge protection - 2KV	

Dimensions	
Height (in.)	1.5
Width (in.)	23.75
Length (in.)	23.75

Aluminum / Steel

Compliance	
Safety Listing	cETLus - Listed
Location Rating	Damp
UL Application	LED Panel Luminaire
Energy Star	No
DLC Approved	Yes
DLC ID	S-FKJMLN; S-CM8LDM
NSF Approved	Yes
Air Tight Rated	No
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Driver Specs - VDC38-48V; 430/620/810mA
Warranty	5 Year Limited - Fixtures

