SATCO' NUVO

Project Name

```
Location
```

Prepared By



NUVO 65-807R2

LED UFO HIGHBAY 240W/4000K

Notes

StatusActiveFixture TypeUFO Hi-BayFinishBlackWattage240WLumen Output33840LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoorSmart Product InfoVoorSpecificationsEDColor TemperatureCool WhiteColor TemperatureCool WhiteColor Temperature277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimmableYes-DimmableDimmablePolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (Ib.)10.11MaterialDie-Cast AluminumDimersionsEConplianceSull-in surge protection - 6KVWeight (Ib.)8.11Width (in.)3.39ComplianceSull-in surge protection - 6KVSafety ListingCulus - CertifiedLocation RatingWetDuc ApprovedYesCalifornia StatusLawful for sale in CaliforniaDiffe 20 / 24 StatusLawful for sale in CaliforniaCalifornia Statudard ICES-005Class ASDS SheetLeadLadion NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	General	
FinishBlackWattage240WLumen Output33840LLumen Output33840LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoorSmart Product InfoVoltoor FixtureSpecificationsEDTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature40C (40F) to +45C (+113F)DinmableYes-DimmableDinming Note010V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-In surge protection - 6KVWeight (Ib.)10.11MaterialDio-Cast AluminumDimensionsESafety ListingC/Lus - CertifiedLocation RatingWetLocation RatingVesDiC LO SARANoDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaDick JatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Status<	Status	Active
Wattage240WLumen Output33840LLumen Output33840LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoorSmart Product InfoIndoorSmart Product InfoIndoorSpecificationsETechnologyLEDColor TemperatureCool WhiteColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimmableVes-DimmableDimmalog Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialDiol/carbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimmesionsInterventionComplianceSafety ListingColc I RatingWetENERCY STARNoDLC ApprovedYesCalifornia StatusLawful for sale iCaliforniaDiff 20 / 24 StatusLawful for saleCalifornia Status<	Fixture Type	UFO Hi-Bay
Lumen Output33840LCCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoorSmart Product InfoIndoorSmart Product InfoNoSpecificationsEDTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOpticani Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (Ib.)10.11MaterialDie-Cast AluminumDimensionsEEdefy STARNoDLC ApprovedYesDLC ApprovedYesDLC ApprovedYesDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Stat	Finish	Black
CCT (Kelvin)4000KIP RatingIP65Indoor or Outdoor FixtureIndoorSmart Product InfoIndoorCT EnabledNoSpecificationsEDTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimmableYes-DimmableDimmableOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-In surge protection - 6KVWeight (Ib.)10.11MaterialDie-Cast AluminumDimensionsItalianFelserSafey STARSafey StatusWetENERGY STARNoDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCompliantYesCanadian Standard ICES-005Class ASD SheetLED_FixtureAdditional NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	Wattage	240W
P Rating IP65 Indoor Indoor Smart Product Info Indoor Smart Product Info No IOT Enabled No SpecIfications E Technology LED Color Temperature Cool White CRI 80+ Voltage 277V-480V Beam Angle 90 Rated Hours 50000 Operating Temperature 40C (-40F) to +45C (+113F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Photocell or Sensor Optional Add-On Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 6KV Weight (ib.) 10.11 Material Die-Cast Aluminum Dimensions E Height (in) 8.11 Width (in.) 13.39 Compliance E Safety Listing ClLus - Certified Location Rating Wet No DLC Approved	Lumen Output	33840L
Indoor or Outdoor FixtureIndoorSmart Product InfoIOT EnabledNoSpecificationsEEDColor TemperatureCool WhiteColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmablePhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions	CCT (Kelvin)	4000K
Smart Product InfoIOT EnabledNoSpecificationsTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (Ib.)10.11MaterialDel-Cast AluminumDimensionsPolycarbonate (PC)Safety Listingcullus - CertifiedLocation RatingWetENRGY STARNoDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadRohrs CompliantYesCandian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesCandian Standard ICES-005Class ASDS SheetLeadInstallation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	IP Rating	IP65
IOT EnabledNoSpecificationsTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (+40F) to +45C (+113F)DimmableYes-DimmableDimmableYes-DimmableDimmableYes-DimmableDimmablePolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensionsInternational (PC)Safety ListingCULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusYesCandian StatusLawful for saleCalifornia	Indoor or Outdoor Fixture	Indoor
SpecificationsTechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (+40F) to +45C (+113F)DimmableYes-DimmableDimmableYes-DimmableDimmableYes-DimmableDimmableYes-DimmableDimmableYes-DimmableDimeterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensionsItalHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesCandian Statudard ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesCanadian Standard ICES-005Class ASDS SheetIcking Hanging Hook; 6 Foot Whip	Smart Product Info	
TechnologyLEDColor TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (+40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions	IOT Enabled	No
Color TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimmig Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensionsImage of the state	Specifications	
Color TemperatureCool WhiteCRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimmig Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensionsImage of the state		LED
CRI80+Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DinmableYes-DinmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions8.11Width (in.)13.39ComplianceSafety ListingSafety ListingcULus - CertifiedLocation RatingWetENRGY STARNoDLC LDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationInstallation NotesInstallation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Voltage277V-480VBeam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions13.39ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetENERY STARNoDLC ApprovedYesCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeavful for saleCalifornia StatusLeavful for saleCandian Standard ICES-005Class ASD SheetLED_FixtureAdditional InformationHounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Beam Angle90Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions13.39ComplianceSafety ListingSafety ListingCULus - CertifiedLocation RatingWetENRGY STARNoDLC DDS-xMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeadRoHS CompliantYesFCC CompliantYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCompliantYesCanadian Standard ICES-005Class ASD SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Rated Hours50000Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (Ib.)10.11MaterialDie-Cast AluminumDimensions13.39ComplianceSafety ListingLocation RatingWetENRGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Standard ICES-005Class ASD SheetLED_FixtureAdditional InformationYesDistallation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Operating Temperature-40C (-40F) to +45C (+113F)DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions13.39ComplianceVetSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeadRotS CompliantYesCalifornia StatusLeadDire StatusLeadRotS CompliantYesCalifornia StatusLeadTitle 20 / 24 StatusLeadCanadian Standard ICES-005Class ASD SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	-	
DimmableYes-DimmableDimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions13.39ComplianceULus - CertifiedSafety ListingCULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationLeoking Hanging Hook; 6 Foot Whip		
Dimming Note0-10V Dimming OnlyPhotocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensionsHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLG IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesStatlation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Photocell or SensorOptional Add-OnLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (Ib.)10.11MaterialDie-Cast AluminumDimensionsHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesInstallation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 6KVWeight (Ib.)10.11MaterialDie-Cast AluminumDimensionsHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Surge ProtectionBuilt-in surge protection - 6KVWeight (lb.)10.11MaterialDie-Cast AluminumDimensions8.11Height (in.)8.11Width (in.)13.39ComplianceUlus - CertifiedSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Weight (lb.)10.11MaterialDie-Cast AluminumDimensionsHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Trop 65LeadROHS CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
MaterialDie-Cast AluminumDimensionsHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
DimensionsHeight (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadROHS CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Height (in.)8.11Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip		
Width (in.)13.39ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadROHS CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	Dimensions	
ComplianceSafety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadROHS CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureInstallation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	Height (in.)	8.11
Safety ListingcULus - CertifiedLocation RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	Width (in.)	13.39
Location RatingWetENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	Compliance	
ENERGY STARNoDLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	Safety Listing	cULus - Certified
DLC ApprovedYesDLC IDS-XMQ3SWNSF ApprovedYesCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetInstallation NotesLocking Hanging Hook; 6 Foot Whip	Location Rating	Wet
DLC ID S-XMQ3SW NSF Approved Yes California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	ENERGY STAR	No
NSF Approved Yes California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	DLC Approved	Yes
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationMounting Height: Up to 35 feetInstallation NotesLocking Hanging Hook; 6 Foot Whip	DLC ID	S-XMQ3SW
Title 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationInstallation NotesInstallation NotesMounting Height: Up to 35 feetIncludesLocking Hanging Hook; 6 Foot Whip	NSF Approved	Yes
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Installation Notes Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Installation Notes Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	Title 20 / 24 Status	Lawful for sale
FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Installation Notes Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	California Prop 65	Lead
FCC Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Installation Notes Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	RoHS Compliant	Yes
SDS Sheet LED_Fixture Additional Information Installation Notes Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip		Yes
Additional Information Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	Canadian Standard ICES-005	Class A
Installation Notes Mounting Height: Up to 35 feet Includes Locking Hanging Hook; 6 Foot Whip	SDS Sheet	
Includes Locking Hanging Hook; 6 Foot Whip	Additional Information	
Includes Locking Hanging Hook; 6 Foot Whip	Installation Notes	Mounting Height: Up to 35 feet
	Warranty	5-Years

