## SATCO NUVO

Project Name

Prepared By



## **NUVO 65-972** LED 60W UFO W/PLUG/120V

Notes

Fixture TypeShop LightFinishWhiteWattage60WWattage60WLumen Output6900LCCT (Kelvin)5000KIP RatingIP65Indoor or Outdoor FixtureIndoor, OutdoorSmart Product InfoVotdoorSmart Product InfoVotdoorSmart Product InfoVotdoorSpecificationsEEDTechnologyLEDColor TemperatureNoSpecifications80+Color Temperature80+Vottage100Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableImmableNon-DimmableImmableNon-DimmableSurge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61Surge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61DimensionsSecast AluminumDimensionsSecast AluminumDimensionsSecast AluminumDice-Cast AluminumSecast AluminumDilloc.Secast AluminumDice-Cast AluminumSecast AluminumSecast AluminumSecast Aluminum<	General	
Fixture TypeShop LightFinishWhiteWintage60WWattage60WLumen Output6900LCCT (Kelvin)5000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoSoorantSpecificationsEEDTechnologyLEDColor TemperatureNatural LightCRI80+Voltage100Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableDimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (In.)1.61MaterialDie-Cast AluminumDimensions	Status	Active
Wattage60WLumen Output6900LCCT (Kelvin)5000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoIndoor; OutdoorSmart Product InfoISpecificationsEEDColor TemperatureNatural LightCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61MaterialDie-Cast AluminumDimensionsSc.63Width (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB.3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRots Jatuanted ICES-005Class ASDS SheetLED_FixtureAdditional InformationYesSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	Fixture Type	Shop Light
Lumen Output6900LCCT (Kelvin)5000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoSmart Product InfoSmart Product InfoSmart Product InfoSigned colspan="2">Signed colspan="2"Colspan= colspan="2"Signed colspan="2"Signed colspan="2"Signed colspan="2"Signed colspan="2"Signed colspan="2"Sign	Finish	White
CCT (Kelvin)5000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSmart Product InfoIndoor; OutdoorSmart Product InfoNoSpecificationsLEDColor TemperatureNatural LightCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61MaterialDie-Cast AluminumDimensions	Wattage	60W
IP Rating     IP65       Indoor or Outdoor Fixture     Indoor; Outdoor       Smart Product Info     Indoor; Outdoor       IOT Enabled     No       Specifications     ED       Color Temperature     Natural Light       CRI     80+       Voltage     120V       Beam Angle     110       Rated Hours     30000       Operating Temperature     -20C (4F) to +45C (+113F)       Dimmable     Non-Dimmable       Lens Material     Polycarbonate (PC)       Surge Protection     Built-in surge protection - 2KV       Weight (Ib.)     1.61       Material     Die-Cast Aluminum       Dimensions     Second       Vidth (in.)     8.27       Comply Listing     CULus - Certified       Location Rating     Wet       DLC Approved     No       B.U.G. Rating     B3-U2-G1       California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Frop 65     Lead       ROHS Compliant     Yes       CC Compliant     Yes       Candian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     Yes       Specification Note     Whit	Lumen Output	6900L
Indoor or Outdoor Fixture Indoor; Outdoor Smart Product Info IOT Enabled No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V Beam Angle 110 Rated Hours 30000 Operating Temperature 20C (4F) to +45C (+113F) Dimmable Non-Dimmable Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Weight (lb.) 1.61 Die-Cast Aluminum Dimensions Height (in.) 5.63 Width (in.) 5.63 Width (in.) 8.27 Compliance Safety Listing CULus - Certified Location Rating B3-U2-G1 California Status Lawful for sale In California Title 20 / 24 Status Lawful for sale California Forp 65 Lead RoHS Compliant Yes Canadian Standard ICES-005 Class A SDS Sheet LED_Fixture Additional Information Specification Note White Powder Coating Finish Includes Encludes Locking Snap Hook	CCT (Kelvin)	5000K
Smart Product Info         IOT Enabled       No         Specifications       EED         Color Temperature       Natural Light         CRI       80+         Voltage       120V         Beam Angle       110         Rated Hours       30000         Operating Temperature       -20C (-4F) to +45C (+113F)         Dimmable       Non-Dimmable         Lens Material       Polycarbonate (PC)         Surge Protection       Built-in surge protection - 2KV         Weight (lb.)       1.61         Material       Die-Cast Aluminum         Dimensions       E         Height (in.)       5.63         Width (in.)       8.27         Compliance       E         Safety Listing       CuLus - Certified         Location Rating       Wet         DLC Approved       No         B.U.G. Rating       B3-U2-G1         California Status       Lawful for sale in California         Title 20 / 24 Status       Lead         California Status       Lead         RoHS Compliant       Yes         FCC Compliant       Yes         CADIMIANT       Yes         Canadian Standard IC	IP Rating	IP65
NoSpecificationsTechnologyLEDColor TemperatureNatural LightColor Temperature80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61MaterialDie-Cast AluminumDimensionsS.63Width (in.)8.27Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCC CompliantYesFCC CompliantClass ASDS SheetLED_FixtureAdditional InformationKet Powder Coating FinishIncludesLocking Snap Hook	Indoor or Outdoor Fixture	Indoor; Outdoor
SpecificationsTechnologyLEDColor TemperatureNatural LightColor TemperatureNatural LightCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	Smart Product Info	
TechnologyLEDColor TemperatureNatural LightCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsS.63Width (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingBa/U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCandaian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	IOT Enabled	No
Color TemperatureNatural LightCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingEawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCilfornia StatusLawful for saleCalifornia StatusLawful for saleCompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantLED_FixtureAdditional InformationLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Specifications	
Color TemperatureNatural LightCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingEawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaCilfornia StatusLawful for saleCalifornia StatusLawful for saleCompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantLED_FixtureAdditional InformationLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Technology	LED
CRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRothS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationSpecification NoteIncludesWhite Powder Coating FinishIncludesLocking Snap Hook		
Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Standard ICES-005LeadCompliantYesCC CompliantYesCanadian Standard ICES-005Lags ASDS SheetLDFixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	CRI	
Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB.3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusYesCandian Standard ICES-005Class ASDS SheetClass AAdditional InformationWhite Powder Coating FinishIncludesWhite Powder Coating Finish		
Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingCuLus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRedS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationSpecification NoteMuite Powder Coating FinishIncludesLocking Snap Hook		
Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)5.63Safety ListingComplianceSafety ListingCullus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingEawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesWhite Powder Coating Finish		
DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusYesFCC CompliantYesFCC CompliantYesSD SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook		
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusYesFCC CompliantYesFCC CompliantYesSpeet ListingClass ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook		
Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions		
Weight (lb.)1.61MaterialDie-Cast AluminumDimensions		
MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceULus - CertifiedSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRCC CompliantYesFCC CompliantSechetSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook		
DimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishSpecification NoteMote Snap Hook		
Height (in.)5.63Width (in.)8.27ComplianceCullus - CertifiedSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook		
Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Dimensions	
ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Height (in.)	5.63
Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantClass ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishSpecification NoteLocking Snap Hook	Width (in.)	8.27
Location RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantClass ASDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Compliance	
DLC Approved     No       B.U.G. Rating     B3-U2-G1       California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       ROHS Compliant     Yes       FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     White Powder Coating Finish       Includes     Locking Snap Hook	Safety Listing	cULus - Certified
B.U.G. Rating     B3-U2-G1       California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     White Powder Coating Finish       Includes     Locking Snap Hook	Location Rating	Wet
California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     White Powder Coating Finish       Includes     Locking Snap Hook	DLC Approved	No
Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     White Powder Coating Finish       Specification Note     Locking Snap Hook	B.U.G. Rating	B3-U2-G1
California Prop 65     Lead       RoHS Compliant     Yes       FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     Specification Note       Specification Note     White Powder Coating Finish       Includes     Locking Snap Hook	California Status	Lawful for sale in California
RoHS Compliant     Yes       FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     Specification Note       Specification Note     White Powder Coating Finish       Includes     Locking Snap Hook	Title 20 / 24 Status	Lawful for sale
FCC Compliant     Yes       Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     Specification Note       Specification Note     White Powder Coating Finish       Includes     Locking Snap Hook	California Prop 65	Lead
Canadian Standard ICES-005     Class A       SDS Sheet     LED_Fixture       Additional Information     Specification Note       Specification Note     White Powder Coating Finish       Includes     Locking Snap Hook	RoHS Compliant	Yes
SDS Sheet     LED_Fixture       Additional Information	FCC Compliant	Yes
Additional Information Specification Note Uncludes Uncludes	Canadian Standard ICES-005	Class A
Specification Note         White Powder Coating Finish           Includes         Locking Snap Hook	SDS Sheet	LED_Fixture
Includes Locking Snap Hook	Additional Information	
· · · · · · · · · · · · · · · · · · ·	Specification Note	White Powder Coating Finish
Warranty 3-Years	Includes	Locking Snap Hook
	Warranty	3-Years

