SATCO NUVO

Project Name

Prepared By



NUVO 65-973 LED 80W UFO W/PLUG/120V

Notes

StatusActiveFixture TypeShop LightFinishWhiteWattage80WLumen Output8523LCCT (Kelvin)3000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsTechnologyTechnologyLEDColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	General	
Fixture TypeShop LightFinishWhiteWattage80WLumen Output8523LCCT (Kelvin)3000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsTechnologyLEDColor TemperatureColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-In surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingSafety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesSD SheetLED_FixtureAdditional InformationYesSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	Status	Active
FinishWhiteWattage80WLumen Output8523LCCT (Kelvin)3000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsTechnologyColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions		
Wattage80WLumen Output8523LCCT (kelvin)3000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsTechnologyLEDColor TemperatureColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)S.63Width (in.)Safety ListingCULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 /24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSD SheetLED_FixtureAdditional InformationYesSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook		
Lumen Output8523LCCT (Kelvin)3000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsETechnologyLEDColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions		
CCT (Kelvin)3000KIP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsIndoor; OutdoorTechnologyLEDColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	-	
IP RatingIP65Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsTechnologyLEDColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions		3000K
Indoor or Outdoor FixtureIndoor; OutdoorSpecificationsLEDColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DinmableNon-DinmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	IP Rating	IP65
TechnologyLEDColor TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions		Indoor; Outdoor
Color TemperatureWarm WhiteCRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions8.27KerneSafety ListingLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSD SheetLED_FixtureAdditional InformationYeis ProveSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	Specifications	
CRI80+Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	Technology	LED
Voltage120VBeam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (Ib.)1.61MaterialDie-Cast AluminumDimensions	Color Temperature	Warm White
Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationYesSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	CRI	80+
Beam Angle110Rated Hours30000Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationYesSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	Voltage	120V
Operating Temperature-20C (-4F) to +45C (+113F)DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesWhite Powder Coating FinishLocking Snap HookLocking Snap Hook	Beam Angle	110
DimmableNon-DimmableLens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)Safety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesWhite Powder Coating FinishLocking Snap HookLocking Snap Hook	Rated Hours	30000
Lens MaterialPolycarbonate (PC)Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesWhite Powder Coating Finish	Operating Temperature	-20C (-4F) to +45C (+113F)
Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)1.61MaterialDie-Cast AluminumDimensions	Dimmable	Non-Dimmable
Weight (lb.)1.61MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Lens Material	Polycarbonate (PC)
MaterialDie-Cast AluminumDimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesWhite Powder Coating Finish	Surge Protection	Built-in surge protection - 2KV
DimensionsHeight (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesWhite San Hook	Weight (lb.)	1.61
Height (in.)5.63Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Material	Die-Cast Aluminum
Width (in.)8.27ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	Dimensions	
ComplianceSafety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationWhite Powder Coating FinishIncludesLocking Snap Hook	Height (in.)	5.63
Safety ListingcULus - CertifiedLocation RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationSpecification NoteWhite Powder Coating FinishIncludesLocking Snap Hook	Width (in.)	8.27
Location RatingWetDLC ApprovedNoB.U.G. RatingB3-U2-G1California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationSpecification NoteWhite Powder Coating FinishIncludesLocking Snap HookLocking Snap Hook	Compliance	
DLC Approved No B.U.G. Rating B3-U2-G1 California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note White Powder Coating Finish Includes	Safety Listing	cULus - Certified
B.U.G. Rating B3-U2-G1 California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note White Powder Coating Finish Includes	Location Rating	Wet
California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note Mhite Powder Coating Finish Includes	DLC Approved	No
Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note Specification Note White Powder Coating Finish Includes Locking Snap Hook	B.U.G. Rating	B3-U2-G1
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note Specification Note White Powder Coating Finish Includes Locking Snap Hook	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note Specification Note White Powder Coating Finish Includes Locking Snap Hook	Title 20 / 24 Status	Lawful for sale
FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Specification Note White Powder Coating Finish Includes Locking Snap Hook	California Prop 65	Lead
SDS Sheet LED_Fixture Additional Information Specification Note White Powder Coating Finish Includes Locking Snap Hook	RoHS Compliant	Yes
Additional Information Specification Note White Powder Coating Finish Includes Locking Snap Hook	FCC Compliant	Yes
Specification Note White Powder Coating Finish Includes Locking Snap Hook	SDS Sheet	LED_Fixture
Includes Locking Snap Hook	Additional Information	
	Specification Note	White Powder Coating Finish
	Includes	Locking Snap Hook
	Warranty	

