## SATCO NUVO

Operating Temperature

Dimmable

Lens Material

Weight (lb.)

Surge Protection

Project Name

ocation

Prepared By



Notes

NUVO 67-115
REC EL EXIT SIGN - DF GR MIR

rw1 04-23-2025 00:25:18

General	
Status	Active
Fixture Type	Exit Sign
Finish	Silver
Wattage	2.94W
Indoor or Outdoor Fixture	Indoor
Specifications	
Technology	LED
Voltage	120V/277V

+10C (+50F) to +40C (+104F)

Built-in surge protection - 3KV

Non-Dimmable

Acrylic

5.2

Aluminum
11
15.75
4

Compliance	
Safety Listing	ULus - Certified; ULus - Listed
Location Rating	Damp
ENERGY STAR	No
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Fixture

Additional Information	
Additional Information	Input Wattage: 2.94W; Output Wattage: 0.4W; Energy Used in Maintenance Mode: 2.94W
Specification Note	Aluminum, Acrylic Panel, 4.8V AA300mAh Ni- Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in; Letter Stroke: 0.75 in.
Includes	Mounting hardware and accessories
Warranty	2 Year Limited