

Project Name

Location

Prepared By



SATCO 67-120

EXIT/LIGHT DH - GREEN

Notes

(www) 03-05-2023 01:20:11

General

| | |
|---------------------------|-----------|
| Status | Active |
| Fixture Type | Exit Sign |
| Finish | White |
| Wattage | 2.8W |
| Lumen Output | 150L |
| CCT (Kelvin) | 5700K |
| Indoor or Outdoor Fixture | Indoor |

Specifications

| | |
|-----------------------|---------------------------------|
| Technology | LED |
| CRI | 70 |
| Voltage | 120V/277V |
| Operating Temperature | +10C (+50F) to +40C (+104F) |
| Dimmable | Non-Dimmable |
| Lens Material | Polycarbonate (PC) |
| Surge Protection | Built-in surge protection - 3KV |
| Weight (lb.) | 2.99 |
| Material | Thermoplastic |

Dimensions

| | |
|--------------|------|
| Height (in.) | 7.25 |
| Width (in.) | 19 |
| Length (in.) | 4 |

Compliance

| | |
|----------------------|-----------------------------------|
| Safety Listing | cULus - Certified; cULus - Listed |
| Location Rating | Damp |
| UL Application | EXIT Signs |
| Energy Star | No |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |

Additional Information

| | |
|------------------------|--|
| Additional Information | Input Wattage: 2.8W; Output Wattage: 1.5W; Energy Used in Maintenance Mode: 2.8W |
| Specification Note | UL94V-0, Thermoplastic, 3.6V AA900mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.; Path of Egress: 6 Ft |
| Includes | Mounting hardware and accessories |
| Warranty | 2 Year Limited |