

Project Name

Location

Prepared By



Notes

[www] 01-12-2023 03:00:00

General

|                           |           |
|---------------------------|-----------|
| Status                    | Active    |
| Fixture Type              | Exit Sign |
| Finish                    | White     |
| Wattage                   | 3.5W      |
| Lumen Output              | 150L      |
| CCT (Kelvin)              | 5700K     |
| Indoor or Outdoor Fixture | Indoor    |

Specifications

|                       |                                 |
|-----------------------|---------------------------------|
| Technology            | LED                             |
| CRI                   | 70                              |
| Voltage               | 120V/277V                       |
| Operating Temperature | +10C (+50F) to +40C (+104F)     |
| Dimmable              | Non-Dimmable                    |
| Lens Material         | Polycarbonate (PC)              |
| Surge Protection      | Built-in surge protection - 3KV |
| Weight (lb.)          | 2.99                            |
| Material              | Thermoplastic                   |

Dimensions

|              |      |
|--------------|------|
| Height (in.) | 7.25 |
| Width (in.)  | 19   |
| Length (in.) | 4    |

Compliance

|                      |                               |
|----------------------|-------------------------------|
| Safety Listing       | cULus - Certified             |
| Location Rating      | Damp                          |
| Energy Star          | No                            |
| DLC Approved         | No                            |
| California Status    | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale               |
| California Prop 65   | Lead                          |
| RoHS Compliant       | Yes                           |
| FCC Compliant        | Yes                           |

Additional Information

|                        |  |
|------------------------|--|
| Additional Information | Input Wattage: 3.5W; Output Wattage: 1.5W; Energy Used in Maintenance Mode: 3.3W   |
| Specification Note     | UL94V-0, Thermoplastic, 3.6V AA900mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C, Remote Compatible; Letter Height: 6 in.; Letter Stroke: 0.75 in.; Path of Egress: 6 Ft. |
| Includes               | Mounting hardware and accessories  |
| Warranty               | 2 Year Limited   |