SATCO NUVO

Project Name

Prepared By

10A19/LED/RGB/TW/T20/SF

Notes

General	
Status	Active
Watts	10W
Incandescent Equivalent	60W
Volts	120V
Shape	A19
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	2700K-5000K
Temperature	Warm to Cool White/Color Changeable
CRI	90+
Lumens	800L
Beam Spread	220 Yee Dimmedule
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category Technology	Type A LED
Smart Product Info	
IOT Enabled	Yes
Operational Humidity	10% - 85% R.H.
Number of Switching Cycles	7500
Software Upgradeable	Yes
Communication Protocol	WiFi
Voice Assistants Supported	Siri; Alexa; Hey Google; SmartThings
Software Supported	Tuya/Starfish APP
Electrical	
Operating Frequency	60Hz
Operating frequency	00112
Specifications	
Dimming Type	Smart-Starfish App only
Dimming Note	Only with Starfish App
Dimming Note Power Factor	Only with Starfish App 0.7
Power Factor	0.7
Power Factor Operating Position Operating Temperature	0.7 Universal
Power Factor Operating Position Operating Temperature Physical	0.7 Universal -20C (-4F) to +45C (+113F)
Power Factor Operating Position Operating Temperature Physical MOL	0.7 Universal -20C (-4F) to +45C (+113F) 4.57
Power Factor Operating Position Operating Temperature Physical MOL MOD	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS)
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.)	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS)
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.)	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS)
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited cULus - Certified; cULus - Listed
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Vermont Status Vermont Status RoHS Compliant	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale
Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	0.7 Universal -20C (-4F) to +45C (+113F) 4.57 2.36 White Plastic (PS) 0.15 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Lawful for sale in California Lawful for sale Lawful for sale

