SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	9W
Incandescent Equivalent	60W
Fluorescent Equivalent	13W
Volts	120V
Shape	A19
Base	Medium
ANSI Base	E26
Finish	Frost
CCT (Kelvin)	3000K
Temperature	Soft White
CRI	80+
Lumens	760L
Beam Spread	220
Dimmable	Non-Dimmable
Hours Rated	10000
Product Category	Type A
Technology	LED
Electrical	
Operating Frequency	60Hz
Operating Frequency Power Factor	0.52
Power Factor	0.52
Power Factor Operating Temperature	0.52
Power Factor Operating Temperature Physical	0.52 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	0.52 -20C (-4F) to +45C (+113F) 4.38
Power Factor Operating Temperature Physical MOL MOD	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38
Power Factor Operating Temperature Physical MOL MOD Weight (lb.)	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited cULus - Certified; cULus - Listed
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Non-Compliant
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.52 -20C (-4F) to +45C (+113F) 4.38 2.38 0.26 Yes 3 Year Limited CULus - Certified; cULus - Listed Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale

