

Project Name

Location

Prepared By



SATCO S11554

5.5W/LED/CFL/850/2P/DUAL

Notes

(www) 01-20-2023 09:30:19

General

Status	Active
Watts	5.5W
Fluorescent Equivalent	13W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	GX23
ANSI Base	GX23
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	550L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL 2-Pin
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Power Factor	0.97
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	5.98
MOD	1.26
Weight (lb.)	0.13

Additional Information

Rated For Enclosed Fixture	No
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Yes
SDS Sheet	LED_Lamp