

Project Name

Location

Prepared By



SATCO S11732

15WT8/LED/CCT/EM/BP

Notes

(www) 09-18-2023 23:33:26

General

Status	Active
Watts	15W
Fluorescent Equivalent	32W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frost
CCT (Kelvin)	3500K/4000K/5000K
Temperature	Neutral White to Natural Light
CRI	80+
Lumens	2000L
Beam Spread	140
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Bypass
Operating Frequency	50/60Hz
THD	<25%
Operating Temperature	0C (+32F) to +45C (+113F)

Physical

MOL	47.78
MOD	1.16
Leg Spacing	0.51
Material	Aluminum / Polycarbonate (PC)
Weight (lb.)	1.12

Additional Information

Additional Info	3.5 Watts and 500 Lumens in Emergency Mode
Tube Guard Use	FALSE
Installation Notes	Not for use in vapor tight fixtures. Maximum Mounting Height: 13 Feet
Specification Note	Work time after power failure: 90 Minutes; Battery Recharge Time is 24 hours
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cRUus - Recognized Component; cULus - Certified; cULus - Classified
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-ZM2STB
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class A
NSF Approved	Yes
SDS Sheet	LED_Lamp