

Project Name

Location

Prepared By



# SATCO S11763

15T8/LED/48-CCT/DM/BP-DR

## Notes

(revised) 08-11-2023 00-01-01

## General

Status	Discontinued
Substitute	S21763
Watts	15W
Incandescent Equivalent	75W
Fluorescent Equivalent	55W
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	White
CCT (Kelvin)	3500K/4000K/5000K
Temperature	Neutral White to Natural Light
CRI	80+
Lumens	2150L/2200L/2200L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

## Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

## Physical

MOL	47.78
MOD	1
Material	Glass / Plastic
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.55

## Additional Information

Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

## Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-X87CKG
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp