

Project Name

Location

Prepared By



SATCO S11766

14T8/LED/48-5CCT/BP/SE-DE

Notes

(www) 01-28-2023 09:30:47

General

| | |
|-------------------------|-------------------------------|
| Status | Active |
| Watts | 14W |
| Incandescent Equivalent | 75W |
| Fluorescent Equivalent | 32W |
| Volts | 120V-277V |
| Ballast Type | Type B |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 48 |
| Finish | White |
| CCT (Kelvin) | 3000K/3500K/4000K/5000K/6500K |
| Temperature | Warm White to Daylight |
| CRI | 80 |
| Lumens | 1700L/1700L/1800L/1800L/1800L |
| Beam Spread | 210 |
| Hours Rated | 50000 |
| Product Category | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|----------------------------|
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| THD | <25% |
| Operating Temperature | -20C (-4F) to +45C (+113F) |

Physical

| | |
|---------------|-----------------|
| MOL | 47.17 |
| MOD | 1 |
| Material | Glass / Plastic |
| Lens Finish | Frost |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 0.45 |

Additional Information

| | |
|----------------------------|--|
| Additional Info | Non CCT Selectable options are S39913-S39916 |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |

Compliance

| | |
|----------------------------|---|
| Safety Listing | cULus - Certified; cULus - Classified; cRUus - Recognized Component |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | S-9MV7GT |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| Canadian Standard ICES-005 | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |