SATCO NUVO

Project Name

ocation Prepared By



SATCO S11827

12WLED/DW/EL/6/CCT-SEL/RND/RD

Notes

w1 10-27-2025 05:20

| Status | Active |
|--------------------------|-------------------------------|
| Substitute | S11827R1 |
| Recessed Can Size | 6 in. |
| Wattage | 12W |
| Voltage | 120V |
| Finish | White |
| CCT (Kelvin) | 2700K/3000K/3500K/4000K/5000K |
| Color Temperature | Warm to Cool White |
| Lumen Output | 900L |
| ndoor or Outdoor Fixture | Indoor |

| Specifications | | |
|-----------------------|----------------------------|--|
| Technology | LED | |
| CRI | 90+ | |
| Beam Angle | 108 | |
| Rated Hours | 50000 | |
| Operating Temperature | -20C (-4F) to +45C (+113F) | |
| Dimmable | Yes-Dimmable | |
| Sloped Ceiling | No | |

| Dimensions | |
|--------------|------|
| Width (in.) | 6.78 |
| Height (in.) | 0.9 |
| Weight (lb.) | 1 |

| Compliance | |
|----------------------------|-------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Wet |
| ENERGY STAR | No |
| DLC Approved | No |
| Air Tight Rated | Yes |
| IC Rated | Yes |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | California T24 Listed |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| Canadian Standard ICES-005 | Class B |
| SDS Sheet | LED_Lamp |

| Additional Information | |
|------------------------|---|
| Additional Information | Candlepower: 300 |
| Specification Note | Lumens (L) vary with color temperature (K): 2700K 900L / 3000K 920L / 3500K 980L / 4000K 980L / 5000K 950L |
| Installation Notes | *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973) |
| Warranty | 5-Years |

