

Project Name

Location

Prepared By



SATCO S11829

10WLED/DW/EL/4/CCT-SEL/SQ/RD

Notes

(www) 02-10-2025 03:20:19

General

| | |
|---------------------------|-------------------------------|
| Status | Active |
| Recessed Can Size | 4 in. |
| Wattage | 10W |
| Voltage | 120V |
| Finish | White |
| CCT (Kelvin) | 2700K/3000K/3500K/4000K/5000K |
| Color Temperature | Warm to Cool White |
| Lumen Output | 650L |
| Indoor or Outdoor Fixture | Indoor |

Specifications

| | |
|-----------------------|----------------------------|
| Technology | LED |
| CRI | 90 |
| Beam Angle | 108 |
| Rated Hours | 50000 |
| Operating Temperature | -20C (-4F) to +45C (+113F) |
| Dimmable | Yes-Dimmable |
| Sloped Ceiling | No |

Dimensions

| | |
|--------------|------|
| Length (in.) | 4.72 |
| Width (in.) | 4.72 |
| Height (in.) | 0.9 |
| Weight (lb.) | 0.77 |

Compliance

| | |
|----------------------|-------------------------------|
| Safety Listing | cETLus - Listed |
| Location Rating | Wet |
| Energy Star | No |
| DLC Approved | No |
| Air Tight Rated | Yes |
| IC Rated | Yes |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | California T24 Listed |
| California Prop 65 | Lead |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |

Additional Information

| | |
|------------------------|--|
| Additional Information | Candlepower: 230 |
| Specification Note | Lumens (L) vary with color temperature (K): 2700K 600L / 3000K 620L / 3500K 650L / 4000K 650L / 5000K 630L |
| Installation Notes | *If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973) |
| Warranty | 5 Year Limited - Fixtures |