

Project Name

ocation Prepared By



10.510/220/40 055/81/52 82

10.5T8/LED/48-835/BP/SE-DE

Notes

1 02-03-2025 00:48:4

Status	Active	
Watts	10.5W	
Incandescent Equivalent	50W	
Fluorescent Equivalent	25W/28W/30W/32W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Gloss White	
CCT (Kelvin)	3500K	
Temperature	Neutral White	
CRI	82	
Lumens	1700L	
Beam Spread	210	
Hours Rated	50000	
Product Category	Т8	
Technology	LED	

Electrical		
Ballasting Requirements	Ballast Bypass	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	

Physical	
MOL	47.78
MOD	1.1
Material	Glass
Lens Finish	Gloss White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.44

Additional Information	
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures.
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Safety Listing	cULus - Certified; cULus - Classified; cRUus Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLY6NGSKA26H
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Yes
NSF Approved	Yes
Flicker Free	Yes
SDS Sheet	LED Lamp

