

Project Name

Location

Prepared By



SATCO S11964

18T8/LED/48-840/BP/R17D/HO

Notes

(revised) 04-23-2023 00:25:18

General

Status	Active
Watts	18W
Incandescent Equivalent	90W
Fluorescent Equivalent	63W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	48
Finish	White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2500L
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	46
MOD	1.1
Material	Glass
Lens Finish	White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.54

Additional Information

Shatter-Proof Type	PET Coated
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp