



Notes

] 06-02-2025 00

| Status | Discontinued | |
|-------------------------|---------------|--|
| Watts | 17W | |
| Incandescent Equivalent | 90W | |
| Fluorescent Equivalent | 45W | |
| Volts | 120V-277V | |
| Ballast Type | Туре В | |
| Shape | T8 | |
| Base | Medium Bi Pin | |
| ANSI Base | G13 | |
| Nominal Length | 48 | |
| Finish | Frost | |
| CCT (Kelvin) | 5000K | |
| Temperature | Natural Light | |
| CRI | 80+ | |
| Lumens | 2200L | |
| Beam Spread | 210 | |
| Hours Rated | 50000 | |
| Product Category | Linear | |
| Technology | LED | |

| Electrical | | |
|-------------------------|----------------------------|--|
| Ballasting Requirements | Ballast Bypass | |
| Operating Frequency | 50/60Hz | |
| Power Factor | 0.9 | |
| THD | 20% | |
| Operating Temperature | -20C (-4F) to +45C (+113F) | |

| Physical | |
|---------------|-----------------|
| MOL | 47.78 |
| MOD | 1 |
| Material | Glass / Plastic |
| Lens Finish | Frost |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 0.44 |

| Additional Information | | |
|----------------------------|---|--|
| Installation Notes | Not for use in vapor tight fixtures. | |
| Specification Note | Compatible with S8000 and S8002 LED EM Driver | |
| Rated For Enclosed Fixture | Yes | |
| Warranty | 5-Years | |

| Compliance | |
|----------------------|--|
| Safety Listing | cULus - Certified; cULus - Classified; cRUus - Recognized Component |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | PLJ808VRML34 |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |
| | |