## SATCO NUVO

Project Name

Location

Prepared By



## Notes

www] 05-15-2024 04:42:5

General	
Ctatue	Active
Status Watts	Active 70W
	250W
Incandescent Equivalent	250W
HID Equivalent Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	10500L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Width: 8 in. Height: 8 in. Depth: 10.75 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Working Voltage	Direct wire range voltage 100- 277V
Operating Frequency	50/60Hz
Candlepower	3377
Dimming Note	Dimmable with optional modules
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Thermal Management	2 step thermal management: 1 - When the lamp body temperature is > 203F, the output of the lamps will reduce to 75 percent; 2 - When
	the driver temperature is >257F, the output of the lamps will reduce to 55 percent.
Operating Temperature	the output of the lamps will reduce
Operating Temperature  Physical	the output of the lamps will reduce to 55 percent.
, ,	the output of the lamps will reduce to 55 percent.
Physical	the output of the lamps will reduce to 55 percent. -30C (-22F) to +60C (+140F)
Physical MOL	the output of the lamps will reduce to 55 percent30C (-22F) to +60C (+140F)
Physical  MOL  MOD	the output of the lamps will reduce to 55 percent.  -30C (-22F) to +60C (+140F)  11.59 7
Physical  MOL  MOD  Lens Finish	the output of the lamps will reduce to 55 percent.  -30C (-22F) to +60C (+140F)  11.59 7 Clear
Physical  MOL  MOD  Lens Finish  Lens Material	the output of the lamps will reduce to 55 percent.  -30C (-22F) to +60C (+140F)  11.59 7 Clear Polycarbonate (PC)
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color	the output of the lamps will reduce to 55 percent.  -30C (-22F) to +60C (+140F)  11.59 7 Clear Polycarbonate (PC) White Multiple Optional Sensors
Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Photocell or Sensor	the output of the lamps will reduce to 55 percent.  -30C (-22F) to +60C (+140F)  11.59 7 Clear Polycarbonate (PC) White Multiple Optional Sensors Available

Sensor / MW

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	This is not to be used with a ballast
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

Compliance	
Safety Listing	cUL - Classified; cUL - Certified
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - >2600 Lumens
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



