

Project Name

Location

Prepared By



SATCO S13154

152W/LED/HID-HB/840/120-277V

Notes

[www] 02-03-2023 09:49:00

| General | |
|-------------------------|---------------------------------------|
| Status | Discontinued |
| Watts | 152W |
| Incandescent Equivalent | 1000W |
| Fluorescent Equivalent | 250W |
| HID Equivalent | 750W |
| Volts | 120V-277V |
| Shape | HB64 |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | White |
| CCT (Kelvin) | 4000K |
| Temperature | Cool White |
| CRI | 82 |
| Lumens | 25000L |
| Beam Spread | 180 |
| Hours Rated | 50000 |
| Product Category | Hi-Bay Flood |
| Technology | LED |
| Min Compartment Size | Diameter: 19.69 in. Height: 19.69 in. |
| Ballasting Requirements | Ballast Bypass |

| Electrical | |
|-----------------------|---------------------------------|
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| Operating Position | Base Up |
| Surge Protection | Built-in surge protection - 6KV |
| THD | 20% |
| Operating Temperature | -40C (-40F) to +60C (+140F) |

| Physical | |
|---------------|-------|
| MOL | 9.33 |
| MOD | 7.91 |
| Lens Finish | Clear |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 3.3 |

| Additional Information | |
|----------------------------|---|
| Rated For Enclosed Fixture | Yes |
| IP Rating | IP40 |
| Installation Notes | Not for use in vapor tight fixtures. Vertical Only with base up |
| Warranty | 5 Year Limited - Hi-Pro |

| Compliance | |
|----------------------|---|
| Safety Listing | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | PNUQ2VIP |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |