

Project Name

Location

Prepared By

**SATCO S13167**

65W/AP37/LED/CCT/100-277V/EX39

**Notes**

(revised) 05-28-2023 00:27:08

**General**

Status	Active
Watts	65W/32W
Incandescent Equivalent	400W
Fluorescent Equivalent	150W
HID Equivalent	175W-250W
Volts	120V-277V
Shape	AP37
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	8450L/4420L
Beam Spread	280
Hours Rated	50000
Product Category	Type A
Technology	LED
Min Compartment Size	Length: 8 in. Width: 8 in. Height: 11 in.
Ballasting Requirements	Ballast Bypass

**Electrical**

Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
THD	15%
Operating Temperature	-22C (-30F) to +45C (+113F)

**Physical**

MOL	8.03
MOD	4.61
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Housing Color	White
Weight (lb.)	2.08

**Additional Information**

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	Lumen/Watt/CCT Ratio Chart in Documents.
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

**Compliance**

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-6YKMLZ
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp