SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	13.5W
HID Equivalent	50W
Volts	120V-277V
Shape	ED17
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2200K
Temperature	Warm White
CRI	80+
Lumens	1700L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Operating Position Surge Protection	Universal Built-in surge protection - 4KV
Surge Protection	Built-in surge protection - 4KV
Surge Protection Operating Temperature	
Surge Protection Operating Temperature Physical	Built-in surge protection - 4KV
Surge Protection Operating Temperature Physical MOL	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8
Surge Protection Operating Temperature Physical MOL MOD	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13
Surge Protection Operating Temperature Physical MOL MOD Housing Color	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost
Surge Protection Operating Temperature Physical MOL MOD	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13
Surge Protection Operating Temperature Physical MOL MOD Housing Color	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures.
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures.
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cULus - Certified; cULus - Classified; cULus -
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro cULus - Certified; cULus - Classified; cULus - Listed
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed Wet
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed Wet No
Surge Protection Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status	Built-in surge protection - 4KV -30C (-22F) to +65C (+149F) 5.8 2.13 Frost 0.17 Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro CULus - Certified; cULus - Classified; cULus - Listed Wet No Non-Compliant

