## SATCO NUVO

Project Name

Location

Prepared By



34W/LED/HID/ED28/850/EX39/WH

Notes

General	
	Astive
Status	Active
Watts	34W
HID Equivalent	150W 120V-277V
Volts	· · · · · · · · · · · · · · · · · · ·
Shape Reserved	ED28
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	5000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 9.25 in. Width: 9.25 in. Height: 17.28 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)
Physical	
MOL	8.4
MOD	3.54
Housing Color	None
Weight (lb.)	0.45
Additional Information	
Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years
Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus -
	Listed
Location Rating	
DLC Approved	Yes
DLC ID	S-D58PNF
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

