SATCO NUVO

Project Name

ocation Prepared By



Notes

w1 04-09-2025 00:05:

Surge Protection

Status	Active
Watts	40W
HID Equivalent	200W
Volts	120V-277V
Shape	ED37
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	7500L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 17.83 in. Width: 17.83 in. Height: 13.39 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal

Operating Temperature	20C / 22E) to 1 CEC / 1140E)	
Operating remperature	-30C (-22F) to +65C (+149F)	
Physical		
MOL	10.3	
MOD	4.7	
Housing Color	None	
Weight (lb.)	0.64	

Built-in surge protection - 4KV

Additional Information		
Rated For Enclosed Fixture	Yes	
IP Rating	IP65	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5 Year Limited - Hi-Pro	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp