## SATCO NUVO

Project Name

ocation Prepared By



Notes

vw1 05-07-2025 00:42:1

General	
Status	Active
Watts	30W/38W/45W
HID Equivalent	150W/250W/320W
Volts	120V-277V
Shape	ED28
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	5850L/7400L/8750L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 14.02 in. Width: 8.03 in. Height: 8.03 in.
Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Electrical	

Operating Frequency	50/60Hz
Candlepower	500
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 3KV
THD	<20%
Operating Temperature	-30C (-22F) to +45C (+113F)

Physical	
MOL	9.92
MOD	3.58
Housing Color	White
Weight (lb.)	0.8

Additional Information		
Rated For Enclosed Fixture	Yes	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5-Years	

Compliance		
Safety Listing	cETLus - Listed	
Location Rating	Wet	
DLC Approved	Yes	
DLC ID	S-R38L9D	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED Lamp	