## SATCO NUVO

Project Name

Prepared By



3CA10/LED/927/FR/120V/E12

Notes

StatusActiveWatts3WIncandescent Equivalent25WVolts120VShapeCA10BaseCandelabraANSI BaseE12FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimmong Note120V onlyHours Rated15000Product CategoryCandleCertricalUOperating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)PhysicalMODMOD1.38Housing ColorNoneWeight (lb.)0.035
Incandescent Equivalent25WVolts120VShapeCA10BaseCandelabraANSI BaseE12FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleCechnologyEDElectrical0.76Operating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
Volts120VShapeCA10BaseCandelabraANSI BaseE12FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DinmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOLMOD1.38Housing ColorNoneWeight (lb.)0.035
ShapeCA10BaseCandelabraANSI BaseE12FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOLMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
BaseCandelabraANSI BaseE12FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
ANSI BaseE12FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency0.76Operating Temperature-20C (-4F) to +45C (+113F)Physical1.38MOD1.38Housing ColorNoneWeight (lb.)0.035
FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)Physical1.38MOD1.38Housing ColorNoneWeight (lb.)0.035
CCT (Kelvin)2700KTemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)Physical1.38MOD1.38Housing ColorNoneWeight (lb.)0.035
TemperatureWarm WhiteCRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating FrequencyPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)MOLMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
CRI90+Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)Physical1.38MOD1.38Housing ColorNoneWeight (lb.)0.035
Lumens200LBeam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectrical0.76Operating Frequency60HzOperating Temperature-20C (-4F) to +45C (+113F)Physical1.38MOD1.38Housing ColorNoneWeight (lb.)0.035
Beam Spread300DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating FrequencyOperating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalI.38MOD1.38Housing ColorNoneWeight (lb.)0.035
DimmableYes-DimmableDimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating FrequencyOperating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOLMOD1.38Housing ColorNoneWeight (lb.)0.035
Dimming Note120V onlyHours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
Hours Rated15000Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalImage: Colspan="2">MOLMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
Product CategoryCandleTechnologyLEDElectricalOperating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
Electrical     Operating Frequency   60Hz     Power Factor   0.76     Operating Temperature   -20C (-4F) to +45C (+113F)     Physical   MOL     MOD   1.38     Housing Color   None     Weight (lb.)   0.035
Operating Frequency     60Hz       Power Factor     0.76       Operating Temperature     -20C (-4F) to +45C (+113F)       Physical     4.72       MOD     1.38       Housing Color     None       Weight (lb.)     0.035
Power Factor0.76Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
PhysicalMOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
MOL4.72MOD1.38Housing ColorNoneWeight (lb.)0.035
MOD1.38Housing ColorNoneWeight (lb.)0.035
Housing Color None   Weight (lb.) 0.035
Weight (lb.) 0.035
-
Additional Information
Additional Information
Rated For Enclosed Fixture Yes
Warranty 2-Years
Compliance
Safety Listing cULus - Certified; cULus - Listed
Location Rating Wet
UL Application Filament LED Lamp
NSF Approved No
California Status Lawful for sale in California
Title 20 / 24 Status Lawful for sale
RoHS Compliant Yes
FCC Compliant Yes
Canadian Standard ICES-005 Class B

