

Project Name

Location

Prepared By



SATCO S21422

5CFL/L/835/GX23/AB/FR/U

Notes

(revised) 10-20-2023 00:00:49

General

Status	Active
Watts	5W
Fluorescent Equivalent	13W
Volts	120V-277V
Ballast Type	Type A/B
Shape	PL
Base	GX23
ANSI Base	GX23
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	630L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	4.09
MOD	1.52
Housing Color	White
Weight (lb.)	0.11

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cULus - Listed; cULus - Classified
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp